

PRODUCT DATA SHEET



ABN: 26 935 350 623
Phone: 1300 577 719
Fax: 1300 366 353
Email: uniseal@sealingservices.com.au
Web: www.global-services.com.au
17 Ryelane Street, Maddington, W.A. 6109

SUPAPRIME

SUPAPRIME is a single pack water based sealer and binding agent formulated for use on a variety of substrates. Based on special water based adhesion promoted resins and additives Supaprime is designed for sealing Supaboard panels, Concrete, Gyprock, Masonry, Fibre Cement, Magnesium Oxide and Calcium Silicate boards and Aluminium surfaces.

Physical Characteristics

Product type	Solvent-free dispersion of modified acrylic resins
Appearance	Light Green liquid.
Viscosity@25°C	2000 mPa
Density @ 25°C	1.02 Kg/Lt
Solids	Approximately 25%
Application Rate	Approximately 8-14m ² /LT @ 20 micron DFT Recommended Application rate 10m ² /LT
Susceptibility to Frost	Avoid freezing conditions. Store above +2°C
Storage Stability	2 Years or more in suitable conditions (18°C to 50 °C)
Cleaning Agent	Water
Danger Classification	Not Applicable. Non Hazardous.

Application Information

Surface Preparation	Surface must be clean, stable and free of dust, oil and grease. Loose particles should be removed and repairs carried out if required.
Application Conditions	Do not apply if the ambient temperature is below 10°C or during rain or if the temperature of the surface may fall below 10°C during the drying period. Do not apply when the ambient and substrate temperatures are above 38°C. Do not apply if the relative humidity is above 85% or if dew point is likely to be reached during the drying period.

Application Information - continued

Application Process Do not dilute. Apply by brush or paint roller and via airless spray equipment at 5 bar pressure and a minimum 0.21mm to 0.30mm nozzle size.

Overcoating Drying will vary with air temperature, humidity and air circulation. In normal conditions the surface may be touch dry in 1 to 3 hours and recoatable after 24 hours. Under adverse conditions drying may be impaired and in extreme instances may even not be possible

Mask exposed glass surfaces to avoid overspray as product may be difficult to remove

Equipment Cleanup:

Wash all equipment thoroughly with water.

Safety Precautions:

Avoid ingestion and contact with skin or eyes. Wear protective goggles and waterproof gloves.

Pack Sizes:

4 litres, 10 litres, 20 litres, 200 litres, 1000 litres

Contact Point

For further information and technical assistance please contact:

Uniseal Manufacturing

17 Ryelane Street

Maddington WA 6109

Tel: 1300 577 719

Fax: 1300 366 353

Email: uniseal@sealingservices.com.au

www.unisealcoatings.com.au



Uniseal Manufacturing is a division of the Global Group of Companies

DISCLAIMER: Please note that this information is supplied based on field and laboratory tests and is, to the best of our knowledge, deemed to be correct, however, no guarantee of the accuracy of this information in all instances is intended or implied and Uniseal Manufacturing accepts no liability for any failure or loss that may result from the application process. Please contact Uniseal Manufacturing if additional or task-specific information is required.